

# Small Tide and Wave Loggers

## Measure more, deploy longer, download faster

The RBRsolo is our most compact, lightweight, and versatile single channel logger. RBRsolo D|tide and RBRsolo D|wave loggers offer flexible measurement schedules, long wave burst samples, expanded memory and power for extended deployments and faster download of large data files.

### Features

- ~30M samples and 16Hz sampling
- Flexible tide averaging
- USB 2.0 download speed
- Low frequency wave detection
- Intermittent and continuous burst ability
- Cabled realtime variant available



Configurations:

**RBRsolo D|tide**      pressure logger with tidal averaging

**RBRsolo D|wave**      pressure logger with intermittent and continuous wave burst and tidal averaging

The single channel tide and wave loggers provide the ease and flexibility to establish the best sampling regime for your measurements. Both loggers take averages of the pressure readings over longer periods of time and at rates up to 16Hz to provide accurate tide level readings. The wave recorder bursts continuously or intermittently making it easier to measure infrequent phenomena such as boat wakes. The large number of burst samples makes low frequency waves easier to detect. Tide and/or wave data exports to Matlab®, Excel®, or text files make post processing with your own algorithms easier. The included Ruskin software performs wave analysis, to provide basic information about the wave composition (e.g. wave energy,  $H_{1/3}$ ,  $T_{1/3}$ ,  $T_{ave}$  and  $H_{ave}$ ). Like all RBR products, the RBR wave and tide loggers are designed to be easy to configure and easy to use.



# Small Tide and Wave Loggers

Measure more, deploy longer, download faster

## Specifications

### Physical

Power:	One 3.6V LiSOCl <sub>2</sub> AA battery
Communication:	USB 2.0
Storage:	~30M readings
Clock accuracy:	±60 seconds per year
Length:	210mm
Diameter:	25.4mm
Weight:	125g in air

### RBRsolo D|tide

Sampling rate:	24hr to 1s and 2, 4, 8 or 16Hz
Averaging duration:	1s to 24h
Averaging interval:	1s to 24h

### RBRsolo D|wave\*

Sampling rate:	24hr to 1s and 2, 4, 8 or 16Hz
Burst (samples):	512 to 32768 (powers of 2)
Burst interval:	1s to 24hr

\*Tide values are the average of the burst readings

### Pressure

Range:	20/50m
Initial accuracy:	±0.05% FS (full scale)
Resolution:	0.001% FS or 0.001 dbar w.i.g.
Time constant:	<0.01s
Typical stability:	0.1% FS per year

### rt realtime variant

External power:	Requires 6 – 18V DC ~4mA
Memory:	No on-board memory
Data:	RS-232 polled or autonomous streaming
Baud rate:	1200 to 115k
Connector:	MCBH-6MP

