

TEMPERATURE AND OPTICAL pH



**LOW POWER,
6000m rated, COMPACT DESIGN**

The RBRcoda OpH is a realtime optical pH sensor. Its dynamic range (7–9pH_T) is optimised for measuring the oceanographic total pH scale. A compact design, low power consumption, and high depth rating support a wide variety of applications.

FEATURES



High
sensitivity



Low power
consumption



Optimised
dynamic range



Compact and
lightweight



RS-232
output



Depths up to
6000m

An optical pH sensor with built-in temperature measurement, for short- to mid-term deployments. Compact and robust, the RBRcoda OpH pairs seamlessly with RBR instruments for a consolidated moored deployment solution or offers a standalone option for integration into third-party platforms.

TEMPERATURE AND OPTICAL pH

LOW POWER, COMPACT DESIGN

Specifications


Physical

Connector	MCBH-6-MP
Housing	Titanium
Depth rating	6000m
Diameter	28mm
Length	~125mm (instrument only) ~160mm (instrument plus connector)
Weight	180g in air, 110g in water
Sampling rate	24h to 2Hz

Interface

RS-232 polled or autonomous streaming

MCBH-6-MP connector pinout



- ▶ Pin 1 - Ground
- ▶ Pin 2 - Power
- ▶ Pin 3 - Serial data from sensor
- ▶ Pin 4 - Serial data to sensor
- ▶ Pin 5 - N/C
- ▶ Pin 6 - N/C

Temperature

Range*	-5 to 35°C
Initial accuracy	±0.002°C
Resolution	<0.00005°C
Typical stability	±0.002°C/year
Time constant	<1s

* Do not allow the foil to freeze.

pH

Measurement range	7–9pH _f
Initial accuracy	±0.05pH within pH 7.5–9
(at 35PSU and atmospheric pressure) *	
Resolution	<0.003pH

* For salinity and pressure dependence, see [RBR Instrument Guide: Sensors](#).

Power

Supply voltage	4.5 to 30V (12V nominal)
Power	75mJ/sample (0.5Hz or slower) 4mA (48mW) (1Hz or faster)
Sleep current	10µA



RBR Ltd

+1 613 599 8900
info@rbr-global.com
rbr-global.com